Bellows differential pressure gauge
Diff. pressure gauge series DPA7
Base Pressure 5MPa (50 bar)

DAHO
2020. 01. 14

Model	DPA7
Element type	Bellows
Accuracy	± 1.5 of Full Scale
Wetted parts:	St.steel
Application:	Low and high pressure of air and liquid

Specification	Code			Currency (원)
Standard Price	DPA7 / 150 mm			2,031,500
Additional Prices				
Type of mounting	P	:	2" pipe mounting bracket	-
	F	:	Front flange mounting (Only 150mm)	*on request*
Pressure connection	R4	:	R1/4" (PT 1/4"), Female	-
	XX	:	Others	*on request*
Liquid filling	0	:	Dry	-
	1	:	Glycerin	114,300
	2	:	Silicon	314,300
Unit of measurement	B	:	bar	-
	K	:	kPa	-
	M	:	MPa	-
	P	:	psi	-
	D	:	dual scale (MPa-inner & bar-outer)	-
	X	:	others	*on request*
Pressure Ranges	R28	:	0…50 kPa	
	R29	:	0…0.1 MPa	
	R31	:	0…0.2 MPa	
	R33	:	0…0.3 MPa	-
	R34	:	0…0.4 MPa	
	R36	:	0…0.6 MPa	
	R37	:	0…1 MPa	

Options				
1. On dial face				
	OR	:	Other pressure range per pcs	14,300
	ND	:	New dial face design	114,300
	NF	:	New dial face printing cost per pcs	4,300
	GM	:	Green marking per pcs	4,300
	CD	:	New dial face design with company logo	72,000
2. Accessories				
	RS	:	Restricter screw in socket hole for high pulsation	2,300
	UC	:	U-clamp for back connection, steel	14,300
	NO	:	Washing for application "USE NO OIL" per pcs, at least ≥ 10 pcs	3,800
	SG	:	Safety glass	2,900
	FF	:	Front flange with 3-hole, stainless steel	3,800
	BF	:	Back flange with 3-hole, stainless steel	3,800
	3W	:	3-way manifold	300,000
	5W	:	5-way manifold	558,600
	TP	:	St steel tag plate, 60 x 20 x 0.5t	9,000
3. Certificates				
	MC	:	Manufature calibration certificate	8,000
	KC	:	KOLAS / ilac-MRA calibration certificate	refer to KOLAS list price