

Piezoresistive silicon pressure transmitter for scrubber application
St.steel body for industrial application
with Declaration of conformity, CE

DAHO
2024.01.26



Model	EDN.335
Sensor type	Piezo_resistive silicon sensor
Accuracy	≤ 0.5%
Wetted parts:	all st.steel
Application:	Scrubber

Pressure Transmitter	Model	Currency (EUR)	
Model:	EDN.335	Basic price	266.92
Scope	Code	Specifications	Additional Prices
Analog output signals	O1	: 4...20mA, 2-wire system	-
	O2	: 0...10V, 3-wire system	-
	O3	: 0...5V, 3-wire system	-
	O4	: 1...5V, 3-wire system	-
Electrical connection	D	: DIN 43650 A	-
	M	: M12 plug	-
	C	: 2m Cable	3.85
Pressure connection	G4	: G1/4"(PF1/4") with 6mm hole	-
	R4	: R1/4"(PT1/4") with 6mm hole	-
	G2	: G1/2"(PF1/2") with 10mm hole	-
	XX	: Others	on request
Pressure Ranges / mbar	R105	: ± 25 mbar	no extra charges
	R106	: ± 50 mbar	
	R119	: ± 250 mbar	
	R122	: ± 500 mbar	

Options

1. Operating temperature	T4	: -40...+125 °C	46.15
2. Accessories	CD2	: Cooling device up to 200 °C	192.31
	CD3	: Cooling device up to 300 °C	230.77
	TP	: St steel tag plate, 60 x 20 x 0.5t	7.31
3. Cable length			
		2m Standard, additional 1m	1.54
4. Certificates	DMCC	: DAHO manufacturing calibration card	6.15
	KC	: KOLAS calibration certificate	refer to KOLAS list price