

Piezoresistive silicon pressure transmitter
Differential pressure transmitter
Based on two absolute sensors

DAHO

2024.01.01



Model	PD-39X
Sensor type	Piezoresistive silicon sensor
Error band	≤ 0.05% FS (typ.) ≤ 0.1% FS (max.)
Wetted part	St.Steel AISI 316L (1.4435) + Nitrile or Viton®
Application	air, oil, water as well as aggressive media

(Currency : KRW)

Specification	Code	List Price
Sensor Version	PD : Differential	-
Model	39X : Differential pressure transmitter	
	[QPDR: Group "C"]	Standard Price
Analog output signals	O1 : 4...20mA, 2-wire system and RS485	-
	O2 : 0...10V, 3-wire system and RS485	-
Electrical connection	B : Binder 423/723 (5-wire)	-
Pressure Connection	G4 : G1/4" Female	-
Pressure Range	R33 : 0...3 bar	
	R37 : 0...10 bar	2,622,600
	R40 : 0...25 bar	
	R45 : 0...100 bar	3,018,300
	R49 : 0...300 bar	
	RYY : Others	Plus 50%
Option		
Accessories	K114B Converter	851,800
	K107 : Converter	1,087,500
Tag. Name plate	TAG : Tag. Name plate, made of st. steel (60 x 20 x 0.5t)	20,000
Certificates	CC : Calibration Certification by Keller (with 5 measuring points)	202,200
	DMCC : DAHO manufacturing calibration card	8,000
	KC : KOLAS calibration certificate	Refer to KOLAS List Price