



Model	ODi-4H
Sensor type	Piezoresistive silicon sensor
Accuracy	Accuracy 0.2% FS
Wetted part	304SS
Application	Gas or liquid

Specification	Code	Currency (EUR)
---------------	------	----------------

Model	ODi-4H : 80mm	236.92
-------	---------------	--------

Standard Price

Additional Prices

Pressure Connection	G4 : PF 1/4"	-
	N4 : NPT 1/4"	on request

Pressure Range / bar	R21 : -1...0	<i>No extra costs</i>
	R29 : 0...1	
	R30 : 0...1.6	
	R32 : 0...2.5	
	R34 : 0...4	
	R36 : 0...6	
	R37 : 0...10	
	R38 : 0...16	
	R40 : 0...25	
	R42 : 0...40	
	R44 : 0...60	
	R45 : 0...100	
	R46 : 0...160	
	R48 : 0...250	
	R50 : 0...400	
	R52 : 0...600	
	R97 : 0...60 mbar	
	R23 : 0...100 mbar	
	R25 : 0...250 mbar	
	R08 : -1...10 bar	
	R55 : 0...1000 bar	84.62

Option

Accessories	CD2 : Cooling device up to 200 °C	153.85
	CD3 : Cooling device up to 300 °C	176.15
	A42 : G1/4(F) x G1/2(M)	134.62
	A4M : G1/4(F) x M20x1.5(M)	134.62
Certificates	DMCC : DAHO function test report	6.15
	KC : KOLAS calibration certificate	Refer to KOLAS List Price