


Piezoresistive silicon pressure transmitter
for industrial applications
with Declaration of Conformity, CE



Model	21Y
Sensor type	Piezoresistive silicon sensor
Accuracy	Accuracy $\pm 0.5\%$
Wetted part	St.Steel AISI 316L (1.4404/1.4435)+Viton®
Application	air, oil, water as well as aggressive media

Specification	Code	Basic prices (원)
Model	21Y : Piezoresistive silicon sensor, PA version	
Analog output signals	O1 : 4...20mA @ 8...32 Vdc	225,000
Sensor type	PA : Sealed gauge, Zero at 1000 mbar abs. > 6 bar	가격표 참조
	PR : Vented gauge, Zero at atm. pressure ≤ 6 bar	견적 문의요
	PAA : Absolute. Zero at vacuum	견적 문의요

※ 상기 output, 4...20mA는 재고 보유중이며, 업체 발주서 수령 후, working day 기준으로 2~3일 이내에 공급할 수 있습니다.

※ Output signal 0...10V 그리고 0.5...4.5V/8...32V 의 제품은 비재고 운영제품이며, 판매 가격은 문의하시기 바랍니다.

※ 21Y, 4...20mA, 제품은 20, 50, 100 pcs 단위로 구매수량에 따른 별도 할인을 적용하여 판매 공급합니다.

Specification	Code	Additional costs (원)
Electrical connection	D : mPm Plug (DIN 43650 C-9.4mm)	-
Pressure Connection	G4 : G1/4"	-
Pressure Range	code	bar
	R02 : -1...35	
	R03 : -1...30	
	R04 : -1...25	
	R04 : -1...24	
	R07 : -1...15	
	R09 : -1...9	
	R09 : -1...5	
	R13 : -1...3	
	R16 : -1...1	
	R19 : -1...0	
	R138 : 0...0.5	
	R23 : 0...1	
	R26 : 0...1.6	
	R27 : 0...2	
	R28 : 0...2.5	
	R29 : 0...3	
	R30 : 0...4	
	R31 : 0...5	
	R32 : 0...6	
	R33 : 0...10	
	R35 : 0...16	
	R36 : 0...20	
	R37 : 0...25	
	R61 : 0...30	-
	R39 : 0...40	
	R40 : 0...50	
	R41 : 0...60	
	R43 : 0...100	
	R45 : 0...160	
	R46 : 0...200	

Keller 제품
PR-23RY를
저압측정 전용으로
공급합니다.

Piezoresistive silicon pressure transmitter
for industrial applications
with Declaration of Conformity, CE

DAHO

※ 250 bar 이상은 아래와 같이 추가 금액이 발생합니다.

R47 : 0...250	59,000
R48 : 0...300	
R50 : 0...400	
R51 : 0...450	
R53 : 0...600	432,700
R55 : 0...1000	

Options

Optional accessories	PCA : Adapter, female G1/4" x male R1/4",R3/8",R1/2",G3/8",G1/2"	20,500
	U7M : 7/16"-20 UNF(M) process thread	견적문의
	U7F : 7/16"-20 UNF(F) process thread	견적문의
	M12 : Electrical connection	견적문의
	CNE mpm DIN Connector 	20,500
Cable Length / Daho 제작	2MC : 2m cable standard to mPm plug	5,000
	ACM : additional extension cable/m to mPm plug & 2m flying cable extension	2,000
Additional device	CD2 : Cooling device up to 200 °C	250,000
	CD3 : Cooling device up to 300 °C	300,000
Certificates	DMCC : DAHO manufacturing calibration card	8,000
	KC : KOLAS calibration certificate	refer to KOLAS list price