



Model: EDA.370
 Sensor type: Piezo_resistive pressure silicon sensor
 Accuracy: $\leq 0.5\% / 0.25\% / 0.1\%$ F.S.
 Wetted parts: st. steel 316L
 Application: air, oil, water as well as aggesive media

Pressure Transmitter	Model	기본 판매가격(원)
Model: EDA.370	A4 : accuracy $\leq 0.5\%$	243,900
	A7 : accuracy $\leq 0.25\%$	325,400
	A9 : accuracy $\leq 0.1\%$	487,800
Scope	Code Specifications	선택사양 추가금액(원)
Analog output signals	O1 : 4...20mA, 2-wire system	<i>under construction</i>
	O2 : 0...10V, 3-wire system	
	O3 : 0...5V, 3-wire system	-
	O4 : 1...5V, 3-wire system	
Electrical connection	P : mPm plug	-
	D : DIN43650A	
Pressure connection	R4 : R 1/4" (PT 1/4")	
	R3 : R 3/8" (PT 3/8")	
	R2 : R 1/2" (PT 1/2")	
	G4 : G 1/4" (PF 1/4")	
	G3 : G 3/8" (PF 3/8")	
	G2 : G 1/2" (PF 1/2")	
	XX : Others	문의 & 추가금액발생
Pressure Ranges / bar - pressure ≤ 40 bar, PR reference pressure - pressure > 60 bar, PA sealed pressure	R19 : -1...0	
	R23 : 0...1	
	R26 : 0...1.6	
	R28 : 0...2.5	
	R30 : 0...4	
	R32 : 0...6	
	R33 : 0...10	
	R35 : 0...16	
	R37 : 0...25	
	R39 : 0...40	
	R41 : 0...60	
	R43 : 0...100	
	R45 : 0...160	
	R47 : 0...250	
	R50 : 0...400	
R53 : 0...600		
R55 : 0...1000		

※ 위에서 언급된 압력범위 0...50 bar 까지는 reference pressure (PR) 이며,
 0...50 bar를 초과하는 압력범위는 sealed pressure (PA).
 절대압(PAA)은 추가금액이 발생하며, 제작공급기간은 대략 5~6주 이상.

추가선택사양

Absolute pressure	PAA	: absolute pressure range [5...6 weeks delivery]	105,300
Operating temperature	T4	: -40...+125 °C	63,200
4-wires system for current	C4	: 4...20mA, 4-wire system (+Vcc, +signal, -Vcc, -signal)	11,600
Accessories	AC20	: Washer, aluminium a/w G1/4"A & G1/2"A-EN 837	2,200
	AC25	: Restirctor screw [oripis] made in st. steel	2,000
	AC40	: Cooling device upto 200 °C	306,200
	AC41	: Cooling device upto 300 °C	400,000
	AC45	: LCD Square Indicator, only for 4...20mA output	158,000
	AC46	: LED Square Indicator, only for 4...20mA output	158,000
	TP	: St steel tag plate, 60 x 20 x 0.5t	10,000
	GK4	: Gasket, aluminium for thread G1/4"	3,100
Flying cable / IP67	ACM	: 2m flying cable + additional extension cable /m	2,200
Underwater plug / IP68	5MCW	: 5m underwater cable standard length	171,900
	ACMV	: additional extension underwater cable /m	6,500
Certificates	DMCC	: DAHO manufacturing calibration card	price included
	KC	: KOLAS calibration certificate	KOLAS 교정비용 참조

※ 발주시 최종 합산된 총금액에서 10 원 이하는 절사하세요

KOLAS 국제공인 인증성적서 교정료

분류 번호	측정기명		교정 주기	교정료			
				표준, 종합 교정절차시 실비	기본교정료	표준소급료	VAT별도
20412	압력변환기 / 전송기		12	표준, 종합 교정절차시 실비	기본교정료	표준소급료	VAT별도
	1	압력변환기-절대압용 압력계			171,500	17,150	188,650
	2	압력변환기-게이지압용 압력계			114,700	11,470	126,170
	3	압력변환기-차압용 압력계			118,200	11,820	130,020
	4	압력변환기-기압계용 압력계			114,700	11,470	126,170
	5	압력변환기-고압용 압력계 (100MPa 이상인 계기)		100 MPa 이상인 계기	143,600	14,360	157,960
	6	압력변환기-미압용 압력계 (0.01 MPa 이하인 계기)		0.01 MPa 이하인 계기	124,100	12,410	136,510
	7	압력변환기-동압용 압력계		실비			

■ 다호가 자체제작하는 제품 또는 직접수입공급하는 제품을 구매하는 경우에 "KOLAS 국제공인 교정료" 에서 50% 할인 적용하며, 다호와 연간 할인 계약 또는 특별고정할인 그리고 구매수량에 따른 할인 적용업체는 중복할인적용이 되지 않습니다.

Product code	Photos	Specifications
AC20		Model : Washer, aluminium for pressure connection EN837 Applied for : Sealing for G1/4" & G1/2" Thickness : 4 mm Outer diameter : 14.5 mm
AC25		Product name: : Restrictor screw [oripis] Material : stainless steel Application: : against pulsation Hole diameter : 0.15mm Outer : less 3mm
AC40		Model : Cooling device upto 200 °C Application : cooling down temperature 200 °C only for pressure transmitters Material : SUS 316 No. of fins : 5 Pressure conn. : G1/4", G1/2"
AC41		Model : Cooling device Application : Temperature upto 300°C a/w diaphragm seals Material : SUS 316 No. of fins : 5 Pressure conn. : G1/4", G1/2"
AC45		Model : Square Indicator, LCD Application : 4..20mA output only Display : -1999...9999 Sampling rate : 3 times / sec Electrical conn. : a/w DIN 43650A made of plastic
AC46		Model : Square Indicator, LED Application : 4..20mA output only Display : -1999...9999 Sampling rate : 3 times / sec Electrical conn. : a/w DIN 43650A, plastic made of plastic