



Model: CDS.21  
 can be assembled with series MAX, series MBX & EDA.370, EDN series

Material of body: Stainless steel 316L

Wetted parts: Stainless steel 316L

Application: Food, pharmaceutical, biotechnology industries

■ **Basic instrument**

**A. Type of model** Model 기본판매가격(원)

Flush diaphragm seal	CDS.21	G1/2" flush diaphragm with suction seal port	163,300
----------------------	--------	--	---------

**B. Selection of features** Code Specifications 선택사양 추가금액(원)

Type of mounting	1	: Direct mounting with bottom connection	-
	C	: Capillary with SUS protection with standard 1 m - incl. thread adapters, female & male at both ends	163,300
	CP	: Capillary with SUS protection & PVC sheath with 1 m - incl. thread adapters, female & male at both ends	204,100
Filling liquid for calibration	GL	: Glycerin	-
	SI	: Silicon	40,900
	VO	: Vegetable oil	61,300
	HT	: High Temperature oil	122,500
Pressure connection	G2	: G1/2" (PF1/2") A	-
	XX	: Others	not allowed

■ **Options**

선택사양 추가금액(원)

1. Teflon coated	TFC	Teflon coated on diaphragm	20,000
2. Capillary with	CSSXL	SUS protection, additional every 1 m	40,900
	CSPXL	SUS protection & PVC sheath, additional every 1 m	61,300
3. Cooling tower	AC40	Cooling tower upto 200°C	on request
	AC41	Cooling tower upto 300°C	on request