Pressure transmitters with flush diaphragm series EDN.320

CE

all st. steel housing of wetted parts with Declaration of Conformity, CE

General features

- Piezosistive Silicon Pressure Transmitters for industrial applications
- Pressure range from -1…0 bar to 0…250 bar
- Special cooling device for high temperature applications
- Wiring with DIN43650A L-connector or various connectors
- Housing parts of stainless steel



Application area

- General industrial applications
- Viscous liquid applications
- Food and beverage industry
- Dosing devices and tanks
- Water and liquid level measurement

General specification

Pressure ranges
-1…0 bar to 0…250 bar
Other pressure ranges on request

Accuracy
better than 0.5% FS
including non-lenearity, hysteresis, zero point and
full scale error according to IEC 61298-2

Non-linearity / BFSL
less than ± 0.25% FS

Overpressure
1.3 X pressure range

Output type
4…20mA, 2-wire system
0…10V, 3-wire system
0…5V, 3-wire system
1…5V, 3-wire system

Power supply

Ref. power:	DC 24V
Available power:	DC 12…30V

Response time
≤ 5ms

Isolation
> 100MΩ at 100 VDC

Materials

Wetted parts:	St.steel 316L
Body:	St.steel 304

Pressure transmitter, series EDN.320

Temperature range

Operating:	-20…80℃
	-40…125℃ / option

Temperature compensating range:	0…70 ℃
Operating temperature:	-20…80 ℃
	-40…125 ℃ / option
Ambient:	-40…100 ℃
Storage:	-40…100 ℃

Thermal error

Zero thermal error:	±0.75%FS @ 25℃, typical
Span thermal error:	±0.75%FS @ 25℃, typical

Electrical connection & Protection

DIN43650 A	IP65
M12 Plug	IP67
Cable type	IP67

Pressure connection
G 1/2", DIN 3852-E with sealing by DIN 3869 ring seals

Weight
Approx. 140g

Option
High temperature cooling device up to 200℃

DAHO

DAHO Tronic Limited
Tel: 02-865-7001 Fax: 02-865-7109
mail: info@daho.co.kr

STX W-Tower 209
Gyeongin-ro 53 Gil 90 Guro-gu
Seoul 08215 Korea

www.daho.co.kr

Technical specifications

Input pressure range

Norminal pressure:

-1…0 bar up to 0…250 bar
others on request

Permissible static pressure:

1.3 x pressure range, max.1100 bar

Output signal / Supply

Current:		Vs=12…30 VDC
2-wire	4…20mA	
Voltage:		Vs=12…30 VDC
3-wire	0…10V	
3-wire	0…5V	
3-wire	1...5V	

Performance

[1]Accuracy: ≤ ±0.5%FSO @ 25℃

[1] accuracy according to IEC 60770 - limit point adjustment including non-linearity, hysteresis as well as repeatability

Permissible load / R_L

Current: 2-wire, R_L max=[(Vs-Vs min)/0.02A]Ω
Voltage: 3-wire, R_L min=10kΩ

Influence effects:

Supply:	0.05%FSO/10V
Longterm stability:	≤±0.5%FS / year
Response time:	<5ms

Thermal effects (Offset and Span) / Permissible temperatures

FS thermal error:	±0.75%FS @ 25℃, typical
Zero thermal error:	±0.75%FS @ 25℃, typical
Operating temperature:	-20…80℃
	-40…125℃ / option
Compensated tempearture:	0…70℃

Electrical protection

Electromagnetic compatibility:

Emission and immunity according to
EN 61326-2-3:20B CCISPR II Group 1, Class A
EN IEC 61000-3-2:2019

Insulation: the transmitter is grounded via the process connection

Mechanical stability

Vibration:	No change at 10 g RMS (20…2000) Hz
Shock:	0.1 g (1m/s) Max.

Materials

Pressure port:	Stainless steel 316L
Housing / body:	Stainless steel 304
Sensor diaphragm:	Stainless steel 316L
Wetted parts:	Stainless steel 316L

Miscellaneous

Current consumption

Signal output current max. 25mA

Current

4…20mA, 2-wire system
Signal output voltage max. 7mA

Voltage:

0…10V, 3-wire system
0…5V, 3-wire system
1…5V, 3-wire system

Weather protection grade

■ Ingress protection: IP65 / IP67 / IP68
(depending on electrical connection)

EMC Test report for CE conformance

■ EN 61326-2-3:2013 / Class A
■ EN 61326-2-3: 2013 / IEC 61326-1:2012

Ordering information

Model code **EDN.320 · ___ · ___ · ___ · B ___**

Output signal	
O1	4…20mA / 2-wire system
O2	0…10V / 3-wire system
O3	0…5V / 3-wire system
O4	1…5V / 3-wire system
O6	0.5…4.5V / 24V, 3-wire system

Electrical connection	
P	mPm plug
D	DIN 43650 A
M	M12 plug
C	2m flying cable

Process connection	
G2	G 1/2" (PF 1/2"), flush diaphragm

Pressure range code, unit bar


Code	Range
R19	-1…0
R23	0…1
R26	0…1.6
R28	0…2.5
R30	0…4
R32	0…6
R33	0…10
R35	0…16
R37	0…25
R39	0…40
R41	0…60
R43	0…100
R45	0…160
R47	0…250
RYY	Others on request

How to order


EDN.320.O1.P.G2.BR35

EDN.320, 4…20mA, mPm plug, G 1/4", 0…16 bar. Manufacturer certi.


Outline drawing



DIN 43650 A Type / IP65




M12 Plug Type / IP67



Cable gland Type / IP67


Process connection




G 1/2" A
DIN EN ISO 1179-2

Pin assignment

DIN 43650A connector according to DIN EN 175301-803A



2-wire / current




3-wire / voltage

Pin No.	2-Wire	3-Wire
1	+Vcc	+Vcc
2	Output(mA)	GND
3		Output(VDC)




Pin No.	2-Wire	3-Wire
1	+Vcc	+Vcc
2	Output(mA)	GND
3		Output(VDC)
4		


Flying leads with 2m cable



2-wire / current



3-wire / voltage



	2-Wire	3-Wire
White	Output(mA)	Output(VDC)
Red		+Vcc
Black	+Vcc	GND

Daho Tronic Ltd.
STX W-Tower 209
Gyeongin-ro 53Gil 90 Guro-gu
Seoul 08215 Korea
Tel: +82 2 865-7001 Fax: +82 2 865-7109
info@daho.co.kr
www.daho.co.kr